

## (EN) INSTALLATION INSTRUCTIONS - DECORATIVE CONCRETE TILES

### Substrate preparation:

The substrate should be dry, level, and cleaned of dust, fats, and paint residues. It should be stable enough to support the weight of the tiles. Any existing low-durability paint coatings should be removed. The wall should be primed with MAXGRUNT primer.




Before attaching tiles to an uneven surface, apply a leveling compound. In the case of laying tiles on light insulation, reinforce the wall with additional dowels and mesh.

### Installation:

Before starting the tile installation, plan the surface, then prepare the tiles and ensure they do not have any visible defects. The back surface of the tile should be cleaned with a wire brush. Mix stone from several packages to level out any color differences, which are a result of manual production and are not considered a defect. Lay the tiles from the bottom up. For tiles with ready-made grout, lay them grout side up. If there is no level, horizontal support for the tiles, use a horizontal starting strip.



For attaching tiles, it is recommended to use the flexible and frost-resistant adhesive MAXGLUE. Apply the adhesive according to the instructions on the package. Move the edges of the tiles close to each other so that there are no gaps between them. Do not glue tiles one on top of the other in a vertical row. The best effect is achieved by gluing subsequent horizontal rows with a shift of ½ the width of the tile compared to the previous row.



During work, avoid contaminating the tiles and their side edges. In case of contamination, the adhesive should be immediately washed off using a damp brush or sponge. Use tools with a diamond blade for cutting tiles. The work should be conducted at temperatures from +10°C to +25°C..

### Note!

The manufacturer is not responsible for the possible appearance of efflorescence, which as a natural phenomenon does not arise from the fault of the manufacturer. The manufacturer is not responsible for improper installation and does not accept claims regarding sizes and colors after the tiles have been installed. To avoid differences in tile shades, it is advised to purchase products from the same production batch. The manufacturer does not accept complaints about tiles purchased a long time apart. All installation activities must be carried out in accordance with construction art and safety regulations based on the above guidelines.

Tiles are made from natural raw materials. The mineral base and the effect of natural stone have been obtained from rock materials with respect for the environment..=